


SBC



PMB-3220

VIA Eden™ LP Industrial MicroATX Motherboard With VGA/Sound/LAN

PMB-3220 is a MicroATX motherboard built-in with VIA Eden™ Low Power CPU at speed of 400/667MHz, VGA, Sound, LAN and other enhanced I/O interfaces. It is suitable for systems required a board controller with multi-functions. It has VGA function (up to 32MB share memory) built-in VIA CLE266 chip to simultaneously display both CRT monitor and LCD panel. Together with the VGA function, PMB-3220 is also equipped with VIA VT1612A AC'97 Codec sound chip providing stereo full duplex multimedia environment to achieve conferencing and communication. All these features help the PMB-3220 to perform the best quality of graphic image, animation and sound.

It also provides solutions for networking systems. Embedded with VIA VT 6103, the motherboard supports 10/100 Base-TX fast Ethernet. It has two 184-pin DDR DIMM sockets supporting up to 2GB DDR DRAM, and three PCI bus for other expanded applications.

Other features include 2 EIDE interfaces, 6 USB 2.0, 1 parallel, and 4 COM ports, one of which can be configured as RS-232/422 or RS-485.



No. 24, Lane 365, Yang Guang St., Nei Hu District, Taipei 114, Taiwan, R.O.C.

Tel: +886-2-8751-1111

Fax: +886-2-8751-1199


Email: sales@protech.com.tw

<http://www.protech.com.tw>

ISO CERTIFIED
9001 14001

PMB-3220

VIA Eden™ MicroATX Motherboard w/ VGA/Sound/LAN



Specifications	
System	
CPU Type	VIA Eden™ processor
CPU Frequency	733MHz
Chipset	VIA VT8606 + VT82C686B
DRAM	2 x 184-pin DDR DIMM, support DDR333 SDRAM up to 2GB max.
BIOS	Phoenix-Award PnP BIOS, with VGA BIOS
Power Supply	Support ATX power
Power Requirement	+5V, +12V, -12V
Power Consumption	+5V: 3.71A / +12V: 2.29A (VIA Eden™ 733MHz)
Dimension	244mm x 200mm (9.6"x 7.87")

I/O Chipset	
IDE Interface	1x40-pin IDE (UDMA 33/66/100/133) 1x44-pin IDE (UDMA 33/66/100)
FDD Interface	1
Bus Interface	3xPCI slots
Serial Port	4 x COM ports, COM1/3/4 for RS232, COM2 for RS232/422/485 (for 16550 compatible type of UART)
Parallel Port	1 x parallel (SPP/EPP/ECP)

Keyboard	Mini DIN connector
Mouse	Mini DIN connector
LAN	VIA VT6103 (10/100 Mbps), support Wake-on-LAN with ATX power
Audio	AC '97 Codec, VIA VT1612A with Line-in/Line-out/MIC
USB	6 x USB 2.0

Display	
Graphic	Built-in VIA CLE266, share system memory, support CRT & TTL
LCD Interface	18/24-bit TTL

Environment	
OperationTemp.	0°~60°C(32°~140°F)
Storage Temp.	-40°~85°C(-40°~185°F)
Humidity	Operation humidity 20~90%, storage humidity 20~95%

Ordering Information	
PMB-3220-C733	Micro ATX size MB with VIA Eden 733MHz CPU / VGA /audio /LAN
Certificate: CE, FCC, CLASS A	

PERFORMANCE & POWER CONSUMPTION

CPU Type	3D Mark 2001 SE Build 330	Business Winstone 2001	Content Creation Winstone 2001	Power Consumption +5V and +12V
VIA Eden™ 667MHz	318	18.6	19.8	3.44A / 0.2A

All of trademarks and brand names are the property of their owners. Trademark "Protech" is the property of Protech Systems Co., Ltd. All information contained in this document is subject to change without any prior notice. This catalog is copyrighted in Jan. 2005.